

# WORLD OUTLAW NATIONALS ULTRA STREET

**32 Car 1/8 Mile Qualified Field | Entry Fee \$150 Car & Driver | Guaranteed Purse Payout**

**\$4,000.00 To Win | \$750.00 Runner-up | \$300.00 Semi | \$200.00 1/4's**

ULTRA STREET SHOOTOUT 2019 (Final 1 8 19)

## CLASS OVERVIEW

Ultra Street is a heads-up small tire class designed for American production vehicles. Small block and big block engines are allowed the use of a single power adder which is restricted in size to maintain class parity. Cross breeding of an engine to a different make/manufacturer body is permitted.

Note: This set of class rules is presented to all competitors under the assumption that any modifications not specifically written within these rules shall be deemed illegal, unless the competitor has the expressed written consent from the Event Tech Director.

## RACING FORMAT

This class will be a 32 car heads-up field, 1/8 mile, Pro Style Ladder on a .400 Pro Tree.

## ENGINE POWER ADDER BASE CIDBASE WEIGHT

Small Block (Inline head) N/A 470 2500

Buick, Olds, Pontiac, Mopar N/A 632 2750

(Any single carb / TB intake permitted)

Small Block (AMC) Nitrous 440 3000

Small Block Nitrous (base starts with Chevy 23deg non raised head) 440 2875

Small Block 76mm Turbo (Cast) 440 3050

Small Block Supercharger 440 3025

(91mm/9.75inch volute) (ADD 50lbs for 91mm/9.76 and larger volute)

Small Block Supercharger 440 3250

(94mm/9.75inch volute) (ADD 50lbs for 94mm/9.76 and larger volute) (Deduct 50lbs for cast wheel)

Small Block Supercharger 4.0L 440 3200

(Twin Screw/Roots) (ADD 100lbs for 4.5L Twin Screw/Roots) (Eaton 2.65L Deduct 100lbs)

Big Block N/A 632 2800

(big block with 9.8 standard deck height and conventional head) (add 2.5 lbs. per cu in over 589)

Big Block N/A 632 2800

(big block Ford with standard deck height and conventional head) (over 589 add 75lbs.)

Big Block N/A 632 2850

(big block with tall deck height and conventional head) (over 589 add 75 lbs.)

Big Block N/A 632 2875

(big block with 9.8 standard height and big chief head) (add 2.5 lbs. per cu in over 589)

Big Block N/A 632 2900

(big block with tall deck height and big chief head) (over 589 add 75 lbs.)

(big block Ford with standard deck height and non-conventional head) (over 589 add 75 lbs.)

Big Block N/A 632 2925

## WORLD OUTLAW NATIONALS ULTRA STREET

(big block GM with Symmetrical port/non-conventional head) (over 589 add 75 lbs.)

Big Block N/A 632 2950

(big block Ford with Pro Stock/Symmetrical type cylinder heads) (over 589 add 75 lbs.)

Big Block Nitrous 588 3150

(big block with conventional head w/.125 plate (add 25 lbs. fogger - max nitrous jet .046)

(SR or Dart 20\* head add 50 lbs.)

Buick, Olds, Pontiac, Mopar Nitrous 588 3075 (Mopar conventional B 1 head accepted)

### NOTE:

Maximum CID for all small block N/A entries is 480 inches. (Add 7lbs per cu in over 470 up to 480 cu in.)

Maximum CID for all small block Boosted entries is 440 inches.

Maximum CID for all small block Nitrous entries is 465 inches. (Add 2lbs per cu in over 440 up to 465 cu in.)

Maximum CID for all Big Block Naturally Aspirated combos is 632 inches.

Maximum CID for big block Nitrous entries is 588 inches.

Maximum CID for Buick, Olds, Pontiac, Mopar Nitrous combinations is 588 inches. (541 to 588 cu in add 2lbs per cu in over 540)

Buick, Olds, Pontiac, Mopar combinations are not permitted Boosted applications.

Any engine in question will be measured with a P&G gauge. A correction factor of 1.5% will be used.

Competitors may be asked to remove a cylinder head for bore and stroke measurements should any discrepancies arise.

All weights will be rounded down to the nearest 5lb. increment.

### WEIGHT ADDITIONS/DEDUCTIONS

For Cylinder Head adder and deducts refer to the Cylinder Head section. For Tire adder and deducts refer to the Tire Section.

Add 50lbs for Boosted GEN III Hemi SBM.

Add 50lbs boosted combo on M1 (intercooler not permitted)

Add 50lbs for Cast Tunnel Ram/Sheet-metal/Dual Carbs on SB & BB N/A

Add 50lbs for Small Block 4 Nitrous Jet dry plates

Add 25lbs for 4 link

Deduct 25lbs for N/A BBC and N/A BBF and N/A BOP for NO forward facing scoop

Deduct 25lbs for leaf spring rear suspension

Deduct 50lbs for IRS

Deduct 50lbs for Belt driven centrifugal supercharger

Deduct 50lbs for Non Intercooled boosted combos on gas

Deduct 50lbs for Single 4150 carb used with 4150 intake manifold and 4150 plate system

Deduct 50lbs. for Single 4150 carb used with Fogger system

(No deduct for use with EFI (SB N/A or SB Nitrous only))

Deduct 50lbs for Small Block/BOP/Mopar Single entry nitrous plate system (1 nitrous/1 fuel)

(Small Block combinations with 2 Nitrous Jet dry plate is not eligible for single entry plate deduction)

Deduct 50lbs for Boosted entries using a 312 - 365 cubic inch small block or mod motor combination.

# WORLD OUTLAW NATIONALS ULTRA STREET

Deduct 100lbs from 94mm base weight for V30-94B

Deduct 100lbs for Boosted entries using a 311 cubic inch or smaller small block or mod motor combination.

Deduct 100lbs for Serpentine belt driven centrifugal supercharger

Deduct 100lbs for 8.2 deck nitrous combo.

Deduct 300lbs for Inline 6 and V6.

Deduct 200lbs if using nitrous with Turbo on Inline 6 and V6.

Deduct 500lbs from Cast 76 base for Turbo Inline 4

## REQUIREMENTS & SPECIFICATIONS

### ENGINE: 1

#### BLOCK

Any aftermarket cast iron or cast aluminum block permitted. All blocks are restricted to factory OEM bore spacing for brand being used. LSX block bolt pattern is permitted for LS based engines. World Products Man-O-War bolt pattern is permitted for small block Ford engines. All entries are permitted to bush lifter bores. Billet Blocks prohibited.

#### HARMONIC BALANCER

SFI Spec 18.1 balancer is required.

#### ENGINE MOUNTS & LOCATION

Engine/motor plates and mid-plates are permitted. Engine block and cylinder heads cannot be in contact with the firewall.

#### CYLINDER HEADS

Factory OEM or aftermarket cast iron or aluminum cylinder heads are permitted. Billet and one-off fabricated heads are prohibited. All cylinder heads must maintain factory OEM bolt pattern for head and intake manifold bolts of manufacturer brand being used. Porting is permitted. All cylinder heads must maintain factory OEM valve angles of +/- 2 degrees. The Event Tech Director reserves the right to check valve angle either on or off the vehicle.

Small Block Ford (specific head weight adds – if your head is not called out specifically see notes below)

- Edelbrock GV2 PN#773169, PN#77319 (Nitrous combos add 75lbs)
- Edelbrock SC1 (Nitrous combos add 125lbs)
- FRPP C3, C302B, C302 (Nitrous combos add 50lbs)

Small Block Chevrolet (specific head weight adds – if your head is not called out specifically see notes below)

- Air Flow Research LS3 Mongoose 12 Degree (Nitrous combos add 75lbs. Boosted combos add 50lbs)
- All Pro 12 Degree Wedge Head #RE13 & #RE11 (Nitrous combos add 50lbs)
- All Pro LS -2 and -5 or any LS 12\* square port (Nitrous combos add 75lbs. Boosted combos add 100lbs.)
- Brodix, BR7 (Nitrous combos add 50lbs. Boosted combos add 100lbs.)
- Edelbrock LS-R PN#770468/Mast 510-215 (Nitrous combos add 100 lbs.)
- ETP C5X (Nitrous combos add 75lbs, Boosted combos add 50lbs)

## WORLD OUTLAW NATIONALS ULTRA STREET

- Profiler 219(Nitrous combos add 75lbs)
- Trick Flow – 18 Degree (Nitrous combos add 75lbs)

Chevrolet Big Block Conventional Port

- Brodix SR20 (Nitrous combos add 50lbs)
- Dart 20deg head (Nitrous combos add 50lbs)

Pontiac

- Roland Racing R2 (CV-1) (Nitrous combos add 25lbs)
- Tiger Head (Nitrous combos add 25lbs)

Note: Stock factory OEM heads are those cylinder heads that are factory production line installed on production vehicles as recognized by NHRA. \*NA BB Heads are called out above with specific weight.

Unless Otherwise Noted-

SB Raised intake runner Chevy 23deg, Ford 20deg or LS 15deg / OEM Z06 12deg - add 50lbs (Except N/A and LS Cathedral Port 13/15)

Any Combination using Inline non stock valve angle add 75lbs (not permitted on boosted combos)

Any canted valve (non-inline) head add 100lbs (not permitted on boosted combos)

Nitrous combinations using any 20deg Ford Non raised runner intake runner add 25lbs

TFS-R Ford runs at base

### INTAKE MANIFOLD

Any aftermarket, commercially available, mass produced, single carburetor, 4150 or 4500 series, cast intake manifold permitted. Fabricated, sheet metal, billet, and any tunnel ram intake manifold are permitted for Small Block & BB N/A combinations only. Modular engines are permitted fabricated, billet and/or sheet metal intake manifolds. Porting is permitted. Cast Holley LS EFI ram intake permitted on boosted LS combinations only.

### NITROUS OXIDE

All entries are permitted to use any conventional single stage plate system or any conventional single stage fogger system. The use of water injection is permitted. The use of a plate system with a fogger system is prohibited. Nitrous push systems are prohibited. The use of agents other than nitrous oxide as part of, or mixed in, the system is prohibited. All entries must use only gasoline for the fuel enrichment circuit. All nitrous jets must be as-supplied, un-modified from the manufacturer and must be a concentric circle. No other shapes such as ovals, diamonds, etc... permitted. All entries are permitted to use a maximum of two 10lb nitrous bottles or a single 15lb nitrous bottle. Any method of cooling the nitrous bottle inside the vehicle is strictly prohibited. Bottle temperatures will be randomly checked before and/or after a run. If the bottle temperature is found to be colder than 65 degrees, the run will be disqualified.

Plate System: Any conventional single stage or cross-bar single stage plate nitrous system with a maximum of four spray bars (two nitrous & two fuel) permitted.

Small Block combinations using a conventional single stage, single plate nitrous system (one nitrous jet and one fuel jet) have Unlimited nitrous jet size.

Big Block Chevrolet or Big Block Ford combinations using a conventional single stage, single plate nitrous system (one nitrous jet and one fuel jet) have a maximum of a nitrous jet size of .125.

## WORLD OUTLAW NATIONALS ULTRA STREET

The maximum allowable number of solenoids for any single stage plate system is three (1 nitrous, 1 fuel and 1 redundant purge). Progressive systems are permitted.

Single Stage Fogger: Any conventional single stage nitrous fogger system permitted. One nitrous/fuel nozzle per cylinder permitted. All entries using a single stage fogger system have a maximum jet size of .046. The maximum allowable number of solenoids for any single stage fogger system is five (2 nitrous, 2 fuel and 1 redundant purge). BBC/BBF limited to (2) .125 nitrous solenoids. Progressive systems are permitted.

Purge System: Nitrous purge systems are permitted a maximum of 1 solenoid. Progressive systems are permitted to use one inline "safety" solenoid. Purge line must clearly exit the hood/cowl or body in a fashion to not allow purged nitrous to enter the engine when racing.

Nitrous Lines: All entries are required to have one continuous -8 maximum (Plate System) and -8 maximum (Fogger System) uninterrupted (no coiling) nitrous supply line from the nitrous bottle to the engine. Maximum length of nitrous supply line from nitrous bottle to nitrous supply solenoid is 15ft. The line from the valve to the engine cannot store/hold nitrous oxide when the system is not in use.

### SUPERCHARGER

Centrifugal superchargers are limited to the following dimensions: Maximum impeller inducer diameter of 3.70 inches with a maximum inlet outside diameter of 4.75 inches. Centrifugal superchargers that are utilizing a compressor housing of 9.76" or larger please refer to weight adder/deductions section of the rules. Supercharger impeller must be constructed from aluminum. Centrifugal superchargers are permitted to use any gear drive or transmission system, including the Vortech V30 series or Procharger F3B-91 or F3B-94. Inlets for superchargers must not be exposed to ram air and pass a "line of sight inspection" from the front of the vehicle, I.E. they must be blocked off from a direct source of air this includes closing off factory holes/grills.

### TURBOCHARGER

All cast wheel turbochargers (mid-frame GT47/S400 chassis only) must be as manufactured from factory with an "as cast" wheel. For "cast wheel turbo", any inconsistent modifications to compressor or turbine wheel, blades, hubs, cover, or housing, beyond accepted commercially available manufacturing process, is PROHIBITED. Compressor inducer cannot exceed 76.6 mm. Maximum inlet diameter for compressor housing will not exceed 78.6 mm (2 mm for housing/wheel clearance). Reducers PROHIBITED. Compressor exducer (this includes the backing plate and the tip to tip measurement) cannot exceed 116 mm and at no point extend past the 116 mm backing plate (i.e. no reverse clipping of the wheel permitted). Inducer blade tip measurement will take place at the leading edge where the tip meets the compressor housing and must extend to the final exducer measurement without steps. Compressor map groove will not exceed .250 of an inch. Any turbocharger entry may be asked to remove the compressor cover for tech inspection. The turbine wheel will not exceed 96.5 mm x 88.5 mm. Turbine wheels are only allowed to be constructed from Inconel material. Compressor wheel/impeller must only be constructed of cast aluminum material. Reducers PROHIBITED. Inlets for Turbochargers must not be exposed to ram air (see note) and pass a "line of sight inspection" from the front of the vehicle, I.E. they must be blocked off from a direct source of air this includes closing off factory holes/grills. (Gas/Q16 turbocharged entries permitted ram air with 50lbs add)

# WORLD OUTLAW NATIONALS ULTRA STREET

## INTERCOOLING

Air-to-water intercoolers are permitted for supercharged and turbocharged entries only. Only one intercooler is permitted for all boosted applications. Intercooler with M1 fuel prohibited.

## METH INJECTION

Meth injection permitted on Nitrous combos only. Any use of nozzle/injector in any engine combination forward of throttle body/ carburetor is strictly prohibited. All injectors on boosted combos must be directly mounted to the intake manifold.

## OILING SYSTEM

Any Oil System permitted. Any oil pump, vacuum pump, and oil pan permitted. All entries are required to use an oil retention device. Device can be either a ballistic style blanket or a custom built metal pan. Metal pan must extend from the engine/motor plate rearward to the back of the engine. Metal pan must fit inside the frame rails and be 3 inches above the ground.

## COOLING SYSTEM

Any cooling system permitted. Radiators are not required.

## EXHAUST SYSTEM

Any exhaust system permitted. All exhaust systems must be directed out of body and away from driver and fuel tank. Exhaust may exit underneath car or out the front fenders but must not affect timing or staging beams. Bull horns prohibited.

## FUEL SYSTEM

Any electronic, mechanical or belt driven fuel pumps are allowed. Electronic fuel pumps must shut off with the master electric cut-off switch. Fuel cell must have a pressure cap and be vented to the outside of the body. Front mounted fuel cells must meet SFI Spec 28.1 and be mounted between the frame rails or enclosed in a round tube frame. A round tube frame must be constructed of a minimum of 1 ¼-inch O.D. x .065-inch chrome moly tubing. Artificial cooling or heating of fuel (i.e., cool cans, ice, Freon, etc.) prohibited. Circulating systems that are not part of the normal fuel pump system are prohibited.

## EFI SYSTEM

Any aftermarket electronic or mechanical fuel injection may be used. Fuel injector size and or type are unlimited.

## THROTTLE BODY

Any single aftermarket throttle body permitted. (Unless N/A)

## CARBURETOR

Maximum carburetor size for all power adder entries is a single 4500-style or a Pro-Systems 115mm SV1.

# WORLD OUTLAW NATIONALS ULTRA STREET

## THROTTLE LINKAGE

Throttle control must be operated by the driver's foot

## FUEL

VP Racing Fuels Gasoline, M1, Q16, C-85, E-85, C12, 16, 23, 25, 45, or NO2 are the only fuels permitted. Event Tech Director reserves the right to inspect fuel at any time during competition. Failure to pass Fuel Check is grounds for disallowance of the run during competition and disqualification from the event during eliminations. Fuel is checked using various means. Samples given to Fuel Check Technical Inspectors are compared to data taken from known fuel samples provided by VP, adjusted for temperature, and within a tolerance determined by Event Tech Director. Failure occurs when the sample readings fall outside those tolerances.

## DRIVETRAIN: 2

### CLUTCH, FLWHEEL & FLYWHEEL SHIELD

Flywheel and clutch meeting SFI Spec 1.2, 1.3, 1.4, or 1.5 is mandatory. Clutches are limited to a dual disc maximum. Flywheel shield meeting SFI Spec 6.2 or 6.3 is mandatory. Clutch must be manually operated by the driver's foot. Electronics, pneumatics, hydraulics, or any other device may in no way affect the clutch system. The throw-out bearing must release all fingers, levers, stages, etc. simultaneously. Staged or variable release clutches are prohibited.

### MANUAL TRANSMISSION

OEM or aftermarket transmissions with a maximum of 5 forward speeds permitted on N/A combinations only. Clutchless models permitted. Any gear change must occur from direct action by the driver. Pneumatic, electric, hydraulic, etc. shifters prohibited. Torque converter not permitted with this type of transmission. Manual transmissions must utilize SFI approved bell housing.

### AUTOMATIC TRANSMISSION

Any OEM or aftermarket automatic transmission is permitted. Lock-up style transmission and/or torque convertors are prohibited unless OEM equipped (i.e. A.O.D.). The use of transmission-to-engine adaptors is permitted. The use of trans-brakes is permitted. Pneumatic, electric, hydraulic, etc. shifters permitted. .

## STEERING

Any American production type steering system permitted.

## SHOCKS/STRUTS

Aftermarket stock-type shocks/struts permitted. Rear coil-over shocks are permitted.

## FRONT SUSPENSION

Factory type front suspension only. Coil over shocks are allowed. Aftermarket replacement control arms are allowed. Aftermarket K-Members/Commercially available sub-Frames allowed. (Must have prior approval from tech) Strut towers must be in factory location with factory sheet metal attaching factory frame rail to top of strut tower, can be notched, windowed, or trimmed for header clearance but must maintain factory sheet-metal attachment.

# WORLD OUTLAW NATIONALS ULTRA STREET

## REAR SUSPENSION

Stock-type, ladder bar, and racing 4-link rear suspension systems are permitted.

## WHEELIE BARS

The use of wheelie bars is prohibited.

## FRAME: 4

### CHASSIS

All vehicles must have a chassis that meets the guidelines set by SFI for their respective speed and elapsed time. A valid NHRA serialized sticker is mandatory at an NHRA Member Track.

## FRAME

Stock frame required from the forward edge (closest to the bumper) of shock/strut tower to the back of the rear wheel tub. Back-halved cars are prohibited. Front and rear sub frames may be joined together. Horizontal and vertical notching of rear frame rail is permitted for tire/rear end clearance.

## WHEELBASE

Entries must retain stock wheelbase dimensions of + or – 1 inch. Maximum wheelbase variation from left to right is 1 inch.

## GROUND CLEARANCE

A minimum of 3 inches from the front of the vehicle to 12 inches behind front spindle centerline is mandatory. A minimum of 2 inches for the rest of the vehicle is mandatory (except for oil pan and exhaust headers).

## TIRES & WHEELS: 5

### TIRES

#### POWER ADDER LEGAL TIRES:

MT 3559 275/60-15 ET Street R

MT 3553 255/60-15 ET Street R or 26 x 8.5 - DEDUCT-50lbs

MT 3453 275/60-15 ET Street S/S – DEDUCT -100lbs

#### N/A LEGAL TIRES:

MT 3559 275/60-15 ET Street R – DEDUCT – 25lbs

MT 3453 275/60-15 ET Street S/S – DEDUCT -150lbs

MT 3754X 275/60-15 ET PRO 275

### WHEELS

Aftermarket racing wheels permitted.

## INTERIOR: 6

### UPHOLSTERY

Interior must maintain a factory upholstered appearance. OEM dash board is required and can be made

## **WORLD OUTLAW NATIONALS ULTRA STREET**

of fiberglass or carbon fiber. Any aftermarket racing style seat is permitted. Driver's seat must be located in the stock location. Passenger seat is not required. Door panels are required. Floor and transmission tunnel where visible must be carpeted or upholstered.

### **STEERING COLUMN/WHEEL**

Aftermarket steering columns and steering wheels are permitted.

### **PEDALS & PEDAL LOCATION**

Stock type pedals/linkage is required.

### **BODY: 7**

#### **BODY**

Body must retain original appearances and profiles for year being used. OEM body shell must be intact. Light weight body panels are restricted to hood, fenders, bumpers, doors and deck-lid/truck-lid or hatch. Composite roof panels are permitted on 2005 and newer vehicles. Hood and deck-lid/trunk-lid must be hinged or lift off style. All front ends must be of factory dimensions and cannot be lengthened. Alterations or aerodynamic modifications are prohibited. Body must be finished or painted.

#### **HOOD SCOOPS**

The use of aftermarket forward facing hood scoops is prohibited on power adder combos. The use of cowl induction style hoods are allowed on any vehicle with a maximum height of halfway point of windshield. Factory OEM forward facing hood or factory OEM ram air hood with scoops is permitted. Forward facing hood scoop on N/A combinations permitted.

#### **COWL AREA**

OEM cowl is required and modifications are permitted.

#### **GRILLE**

Grille must maintain a "professional appearance" for year, make and model being claimed.

#### **FIREWALL**

Stock, factory firewall is required. Notching and smoothing of firewall is permitted but must be identifiable as being in the factory location. Factory OEM fiberglass firewalls (Corvette) are permitted to replace the factory firewall with a minimum of .024 thick steel located in the factory location.

#### **RADIATOR CORE SUPPORT**

Radiator core support is not required.

#### **FENDER SPLASH PANS**

Fender splash pans may be altered.

#### **WINDSHIELD & WINDOWS**

OEM glass or NHRA approved Lexan is required.

#### **FLOOR**

Complete stock floor in stock location is required. Flat area of floor-pan starting at "kickup" for rear end (behind rear seat area) and rearward may be replaced with a minimum of .024-inch thick steel or .032-inch aluminum. All entries are allowed a removable trans-tunnel.

#### **WHEEL WELLS**

Aftermarket style mini-tubs are permitted.

#### **WING/SPOILERS**

## **WORLD OUTLAW NATIONALS ULTRA STREET**

All entries are permitted to use rear wing/spoilers. Wing/spoilers are allowed a maximum length of 26 inches. Any adjustments to the wing/spoiler during a run are prohibited.

### **STREET EQUIPMENT**

All entries must have operational headlights/fog lights and taillights.

### **APPEARANCE**

All cars in competition must be painted or wrapped. Advertising graphics are permitted on the body. In order to be eligible for the Ultra Street Shootout points championship program, all sponsors' decals must be easily visible and located on the outside of the vehicle. Failure to do so can result in the driver forfeiting all claimed championship points for that particular event. The Ultra Street Shootout points championship program requires that all entries run the following decals:

1. Championship Windshield Banner: Decal needs to be located on the top of the windshield or just above the windshield located on the body.
2. Championship Series License Plate: Plate must be located on the front of the vehicle
3. Class Sponsor(s): Decal must be located on the passenger's side lower portion of the windshield.
4. Class & Competition Numbers: Numbers must be easily visible/legible and located on the front, back, and both side windows.

### **ELECTRICAL: 8**

#### **BATTERIES**

Battery may be relocated and must be an automotive type.

#### **IGNITION**

Any battery-operated ignition system permitted. Distributorless ignition systems are limited to one coil per cylinder only. Optical devices and magneto ignitions are prohibited.

#### **MASTER CUTOFF**

A master cutoff switch is mandatory on all vehicles with a battery located in the trunk.

#### **STARTER**

Aftermarket starters, in stock location permitted.

### **SUPPORT GROUPS: 9**

#### **BRACKET RACING AIDS**

The use of any bracket racing aids such as optical sensors, delay boxes, shutter boxes, throttle stops, etc. are prohibited. The use of any device (electrical or mechanical) that allows a driver to ascertain the position of their vehicle to the starting line is prohibited.

#### **PRESSURIZED BOTTLES**

All pressurized bottles must meet D.O.T. 1800lb minimum specification.

#### **TOW VEHICLES**

The use of tow vehicles is permitted.